

Fast assembly concealed hinge without self closing feature

- ▶ Sensys 8687 in obsidian black, zero protrusion hinge
- ▶ 165° opening angle



- ▶ Hinge with clip on installation without self closing feature
- ▶ For example, for Push to open applications
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Opening angle can be reduced by means of optional accessory
- ▶ Zero protrusion hinge
- ▶ All visible parts in obsidian black
- ▶ Hinge arm material: steel in obsidian black
- ▶ Hinge cup material: steel in obsidian black

Sensys 8687, 165° opening angle

Cup assembly	Drilling pattern	Mounting hole ø x T mm	full overlay	half overlay	PU	
			Base B 12.5 mm	Base B 3 mm		
For screwing on TH 52		-			1/50 ea.	
With premounted expanding sockets TH 58		ø 10 x 11	9 091 769	9 091 770	9 091 791	9 091 792