

corpus	pos.	article - name	quantity	comment
1	a	no fitting; only one blind	-	
2	a	Sensys 110° hinge with integrated Silent System (Sensys 8645i), nickel plated, overlay, Opening angle 110°, drilling pattern TH 52 x 5,5 mm, for pressing in (ø 10 x 11)	2	
2	a	Cross mounting plate with Direkt height adjustment, nickel plated, Hole line 37 x 32 mm, with expanding sockets (for drilling ø 5 x 12 mm), distance 1.5 mm	2	
2	a	Push to open Pin for drilling in Long travel light grey	1	
2	a	Cover cap for Sensys hinge arm ( embossed with Hettich logo )	2	
2	a	Cover cap for Sensys hinge cup (for drilling pattern TH / TS)	2	
3	a	Quadro S, 30 kg, Full extension, lengths 500 mm, Silent System, Plug on installation	1	
3	b	Blank panel	-	
3	c	Quadro S, 30 kg, Full extension, lengths 500 mm, Silent System, Plug on installation	1	
3	a/c	Recessed handle Borgo, ●-● 0, H 11 mm, ø 41 mm, gloss chrome plated	3	
4	a	Slatted frame incl. accessories	1	
4	a	Mattress	1	
5	a	Height adjustable castor (fixed castor)	1	
5	a	Full extension runner Actro 5D 550 mm left and right XL (70 kg)	1	
5	a	Side stabiliser	4	
5	-	Socket no. 30 M4 ø 8 drilling depth 8 mm	10	
		Handle fixing screws M4 x 24	10	
5	a	VB 35 M / 16 for 16 mm shelves black	4	
5	a	Screw in dowel DU 321, 6.7 mm, galvanised	4	
5	a	Cadro System	-	
5	a	Additional Silent System set	1	
5	a	Spacer roller	2	
5	a	Side stabiliser	2	
5	a	Recessed handle Genzone, L 134 mm, B 16 mm, H 16 mm, gloss chrome plated	1	
5	b	Recessed handle Genzone, L 134 mm, B 16 mm, H 16 mm, gloss chrome plated	1	
5	b	Sensys 110° hinge with integrated Silent System (Sensys 8645i), nickel plated, overlay, Opening angle 110°, drilling pattern TH 52 x 5,5 mm, for pressing in (ø 10 x 11)	2	
5	b	Cross mounting plate with Direkt height adjustment, nickel plated, Hole line 37 x 32 mm, with expanding sockets (for drilling ø 5 x 12 mm), distance 3.0 mm	2	
5	b	Push to open Pin Strong for drilling in Long travel light grey	1	
5	b	Cover cap for Sensys hinge arm ( embossed with Hettich logo )	2	
5	b	Cover cap for Sensys hinge cup (for drilling pattern TH / TS)	2	
5	b	VB 35 M / 16 for 16 mm shelves nickel plated	18	
5	b	Screw in dowel DU 321, 6.7 mm, galvanised	18	
1-5	-	AVB 4 Slim, 100 mm	6	
1-5	-	Rastex 15 without rim nickel plated 19 mm	13	
1-5	-	Screw in dowel Twister DU 232 T 30 mm black	13	

